

2MP SMART HYBRID LIGHT TURRET NETWORK CAMERA WITH AUDIO & STROBE LIGHT ALARM

Short Description

The Hikvision DS-2CD1323G2-LIUF/SL is a powerful yet affordable turret network camera designed for modern security needs. Featuring Smart Hybrid Light technology, it automatically switches between IR and white light — combining night-time clarity with active deterrence illumination up to 30 m. With intelligent detection, two-way audio, and robust weatherproofing, it's an ideal solution for homes, small businesses, and commercial properties.



Key Feature

- Model Number: DS-2CD1323G2-LIUF/SL
- Brand: Hikvision
- Category: Internet Protocol (IP) Camera
- Availability: Available

Product Information

| | |
|---------------------|-------------------------------|
| Model Number | DS-2CD1323G2-LIUF/SL |
| Brand | Hikvision |
| Category | Internet Protocol (IP) Camera |
| Availability | Available |
| Price Type | Contact for price |

Description

The DS-2CD1323G2-LIUF/SL is a powerful 2MP Full HD dome network camera designed to provide advanced security monitoring with intelligent detection and active deterrence features. Equipped with a high-performance Progressive Scan CMOS sensor, the camera captures clear and detailed 1920 × 1080 resolution video for reliable surveillance in both indoor and outdoor environments. Its Smart Hybrid Light technology combines infrared and white light illumination, enabling clear color images at night and providing visibility up to 30 meters in low-light conditions. Powered by Hikvision's AcuSense technology, the camera can accurately distinguish human and vehicle targets from other moving objects, significantly reducing false alarms caused by rain, animals, shadows, or leaves. The built-in microphone allows audio recording alongside video, providing additional evidence and situational awareness. For enhanced security, the camera features an active strobe light and audio alarm that can automatically deter intruders when unauthorized activity is detected.

The camera supports advanced H.265+ video compression, helping reduce bandwidth consumption and storage requirements without compromising image quality. Image enhancement technologies such as Digital WDR, BLC, and 3D DNR ensure clear footage in challenging lighting conditions. Remote access through Hik-Connect and iVMS-4200 software allows users to monitor their property from anywhere using a smartphone, tablet, or computer.

Designed for durability and long-term performance, the DS-2CD1323G2-LIUF/SL features an IP67-rated weatherproof housing, making it suitable for harsh outdoor environments. With support for PoE and 12V DC power options, flexible installation, ONVIF compatibility, and robust cybersecurity features, this camera is an ideal solution for homes, offices, retail stores, warehouses, schools, parking areas, and other commercial security applications.

Technical Specifications

| Camera Specifications | |
|------------------------------|--|
| Image Sensor | 1/2.9" Progressive Scan CMOS |
| Max. Resolution | 1920 × 1080 |
| Min. Illumination | Color: 0.005 Lux (F1.6, AGC ON) / B&W: 0 Lux with IR |
| Lens Type | Fixed focal, 2.8 mm or 4 mm |
| Supplement Light | IR + White Light (Smart Hybrid), up to 30 m |
| Compression | H.265+ / H.265 / H.264+ / H.264 |
| Network | |
| Security | Password protection, complicated password, watermark, basic and digest authentication for HTTP, WSSE and digest authentication for Open Network Video Interface, security audit log, host authentication (MAC address) |
| Simultaneous Live View | Up to 6 channels |
| Protocols | TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, RTCP, NTP, IGMP, IPv4, IPv6, UDP, QoS, FTP, SMTP |
| Client | iVMS-4200, Hik-Connect |
| Web Browser | Plug-in required live view: IE 10, IE 11, Local service: Chrome 57.0+, Firefox 52.0+, Edge 89+ |
| Interface | |
| Ethernet Interface | 1 RJ45 10 M/100 M self-adaptive Ethernet port |
| Reset Key | Yes |
| Built-in Microphone | Yes |
| Power & Physical | |
| Power | 12 VDC ± 25%, 0.66 A, max. 8 W, Ø5.5 mm coaxial power plug, reverse polarity protection, PoE: IEEE 802.3af, Class 3, max. 9.5 W |

PCNS Kathmandu-10, Baneshwor, Nepal info@pcns.com.np +977 9700045888

