

# 2MP SMART HYBRID LIGHT TURRET NETWORK CAMERA

## Short Description

The Hikvision DS-2CD1323G2-LIU is a 2MP Smart Hybrid Light IP dome camera offering high-quality Full HD video with both IR and white light illumination for clear night surveillance. It features H.265+ compression, built-in microphone for audio monitoring, motion detection, and IP67 weatherproof protection, making it suitable for indoor and outdoor security applications.



## Key Feature

- Model Number: DS-2CD1323G2-LIU
- Brand: Hikvision
- Category: Internet Protocol (IP) Camera
- Availability: Available

## Product Information

<b>Model Number</b>	DS-2CD1323G2-LIU
<b>Brand</b>	Hikvision
<b>Category</b>	Internet Protocol (IP) Camera
<b>Availability</b>	Available
<b>Price Type</b>	Contact for price

## Description

---

- 2MP Smart Hybrid Light IP dome camera
- 1/2.9" Progressive Scan CMOS sensor for clear and stable imaging
- Maximum resolution: 1920 × 1080 (Full HD)
- Smart Hybrid Light technology (IR + White Light for flexible night vision)
- Up to 30 m IR night vision range (depending on environment)
- White light illumination for full-color night imaging when needed
- Built-in microphone for real-time audio recording and monitoring
- H.265+/H.265/H.264+/H.264 video compression for efficient storage usage
- Supports dual-stream video for optimized bandwidth management
- Frame rate up to 25/30 fps at 1080p resolution
- Fixed lens options (commonly 2.8 mm / 4 mm depending on model variant)
- Wide-angle field of view for area surveillance coverage
- Digital WDR (Wide Dynamic Range) for balanced lighting in high-contrast scenes
- 3D DNR (Digital Noise Reduction) for clearer low-light video quality
- BLC (Backlight Compensation) for improved visibility in strong backlight conditions
- Motion detection, video tampering alarm, and exception alerts
- Smart detection features (depending on configuration) for human/vehicle classification
- Supports ONVIF protocol for compatibility with third-party NVR systems
- Compatible with Hik-Connect mobile app and iVMS-4200 software
- Ethernet 10/100 Mbps RJ45 network interface
- Supports PoE (Power over Ethernet) for easy installation
- IP67-rated weatherproof housing for indoor and outdoor use
- IK10 vandal-resistant design (on select variants) for added durability
- Operating temperature range suitable for harsh environments (-30°C to 60°C approx.)
- Compact dome design suitable for homes, offices, shops, schools, and commercial buildings
- Supports privacy mask, watermark, IP filtering, and secure password protection

# Technical Specifications

---

<b>IP Camera</b>	
Image Sensor	1/2.9" Progressive Scan CMOS
<b>General Specifications</b>	
Max Resolution	1920 × 1080 (2MP Full HD)
Min Illumination	Color: 0.01 Lux @ F2.0, 0 Lux with IR
Day & Night	IR Cut Filter with Smart Hybrid Light
Night Vision (IR Range)	Up to 30 meters (with Smart Hybrid Light)
Smart Detection	Human & Vehicle Detection (AcuSense)
Power Support	12V DC / PoE (802.3af)

**PCNS** Kathmandu-10, Baneshwor, Nepal info@pcns.com.np +977 9700045888